

MAZDA3 HATCHBACK



| | | | | |
|-----------------------|--|-------|-------|-------|
| DIMENSION & WEIGHT | Overall length (w/o number-plate holder) | | mm | 4,460 |
| | Overall width (w/o wheel arch molding) | | mm | 1,795 |
| | Overall height (w/o shark fin antenna) | | mm | 1,435 |
| | Wheelbase | | mm | 2,725 |
| | Tread | Front | mm | 1,570 |
| | | Rear | mm | 1,580 |
| | Ground clearance (unladen) | | mm | 140 |
| | Minimum turning radius | | m | 5.3 |
| Vehicle curb weight | | kg | 1,400 | |

| | | | | |
|--------|--------------------|--|--|-----------------|
| ENGINE | Type | | SKYACTIV-G 2.0, In-line, 4 cylinder DOHC | |
| | Displacement | | cc | 1,998 |
| | Bore x stroke | | mm | 83.5 x 91.2 |
| | Compression ratio | | 13.0 : 1 | |
| | Maximum output | | kW (ps)/rpm | 114 (155)/6,000 |
| | Maximum torque | | Nm/rpm | 200/4,000 |
| | Fuel | | Petrol | |
| | Fuel tank capacity | | L | 51 |

| | | | | |
|------------|-------------------|---------|-------------------|--|
| DRIVETRAIN | Drivetrain | | FWD | |
| | Transmission type | | 6-speed automatic | |
| | Gear ratios | 1st | 3.552 | |
| | | 2nd | 2.022 | |
| | | 3rd | 1.347 | |
| | | 4th | 1.000 | |
| | | 5th | 0.745 | |
| | | 6th | 0.599 | |
| | | Reverse | 3.052 | |
| | Final gear ratio | | 3.850 | |

| | | | | |
|----------|---------------------|--|----------------------------------|--|
| STEERING | Type | | Rack and pinion | |
| | Power steering type | | Electric Power-Assisted Steering | |

| | | | | |
|------------|------|-------|-------------------|--|
| SUSPENSION | Type | Front | MacPherson strut | |
| | | Rear | Torsion Beam Axle | |

| | | | | |
|--------|----------|-------|-----|------------------|
| BRAKES | Type | Front | mm | Ventilated discs |
| | | Rear | mm | Solid discs |
| | Diameter | Front | 295 | |
| | | Rear | 265 | |

| | | | | |
|----------------|------------|--|-----------|--|
| TYRES & WHEELS | Tyre size | | 215/45R18 | |
| | Wheel size | | 18X7J | |